AD-A084 090

ARMY MEDICAL PIOENGINEERING RESEARCH AND DEVELOPMENT --ETC F/6 6/5
LABORATORY EVALUATION OF THE USDA RAPID NONDESTRUCTIVE STORED P--ETC(U)
FEB 80 L M ANDERSON. J H NELSON
USAMBRDL-TR-8001

NL

END
ORDER

TECHNICAL REPORT 8001

LABORATORY EVALUATION OF THE USDA RAPID NONDESTRUCTIVE STORED PRODUCTS INSECT DETECTOR

LEROY M. ANDERSON
JAMES H. NELSON Ph.D.
JAMES I. KARDATZKE CPT, MSC
DONALD P. DRIGGERS CPT, MSC

(9) Final repl. Aug 17-

US ARMY MEDICAL BIOENGINEERING RESEARCH and DEVELOPMENT LABORATORY

Fort Detrick Frederick, Md. 21701

10 3546-17-18281

11 FEBRUARY 1980

ELEASE;

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

MUSAINE WITH-ERTL

US ARMY MEDICAL RESEARCH AND DEVELOPMENT COMMAND FORT DETRICK FREDERICK, MD 21701



470.]

ADA 084090

111/828

80 5 9

9 u30

NOTICE

<u>Disclaimer</u>

The findings in this report are not to be construed as an official Department of the Army position unless so designated by other authorized documents.

Disposition

Destroy this report when it is no longer needed. Do not return it to the originator. $% \left(1\right) =\left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left(1\right) +\left(1\right) \left(1\right) \left$

SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

	READ INSTRUCTIONS BEFORE COMPLETING FORM			
1. REPORT NUMBER 2. GOVT ACCESSION NO	O. 3. RECIPIENT'S CATALOG NUMBER			
TECHNICAL REPORT 8001 AD-A 084 090)			
4. TITLE (and Subtitle)	S. TYPE OF REPORT & PERIOD COVERED			
LABORATORY EVALUATION OF THE USDA RAPID	Final Report			
NONDESTRUCTIVE STORED PRODUCTS INSECT DETECTOR	August 1977 - December 1979			
	6. PERFORMING ORG. REPORT NUMBER			
7. AUTHOR(*) LEROY M. ANDERSON DONALD P. DRIGGERS, CPT, MSC JAMES H. NELSON, Ph.D. JAMES T. KARDATZKE, CPT, MSC	S. CONTRACT OR GRANT NUMBER(*)			
9. PERFORMING ORGANIZATION NAME AND ADDRESS	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS			
US Army Medical Bioengineering Research	62778A			
& Development Laboratory, ATTN: SGRD-UBG Fort Detrick, Frederick, MD 21701	3S162778A838/00/025			
11. CONTROLLING OFFICE NAME AND ADDRESS	12. REPORT DATE			
US Army Medical Research & Development Command ATTN: SGRD-AJ	MARCH 1980			
Fort Detrick, Frederick, MD 21701	13. NUMBER OF PAGES 22			
14. MONITORING AGENCY NAME & ADDRESS(II ditterent from Controlling Office)				
	UNCLASSIFIED			
	15#, DECLASSIFICATION/DOWNGRADING SCHEDULE			
16. DISTRIBUTION STATEMENT (of this Report)				
Approved for public release; distribution unlimite	ad.			
population public releases arist roution unrintroe				
	Loession For			
17. DISTRIBUTION STATEMENT (of the abstract entered in Block 20, if different i	from Report) NIIS distal			
	DDC PAR			
	Unamaion seed			
	Unamaons ed Justification			
	Justification			
18. SUPPLEMENTARY NOTES	Justification			
18. SUPPLEMENTARY NOTES	Justification			
18. SUPPLEMENTARY NOTES	Justification			
	Ry ''' institution we ilability Codes [Availand/or			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number	Ry ''' institution we ilability Codes [Availand/or			
19. KEY WORDS (Continue on reverse side if necessary and identify by block number Carbon dioxide Red flour beetle	Fr. // // ibutton/ writability Codes [Availand/or			
19. KEY WORDS (Continue on reverse side it necessary and identify by block number Carbon dioxide Red flour beetle Commodity chamber Stored products	Fr. White is a state of the st			
19. KEY WORDS (Continue on reverse aids it necessary and identify by block number Carbon dioxide Red flour beetle Commodity chamber Stored products Insect detector	Fr. White is a state of the st			
19. KEY WORDS (Continue on reverse aids if necessary and identify by block number Carbon dioxide Red flour beetle Commodity chamber Stored products	Fr. // // ibutton/ writability Codes [Availand/or			

Tests conducted in the laboratory determined that the insect detector (second prototype) could distinguish between a sample with three live insects per pound and an uninfested sample of stored food products. The detector could not differentiate between no infestation and one insect in 5-pound packaged com-

modities or a 1-pound sample of whole grain. The length of time necessary to test a sample and extrinsic interferences from various sources made the first and second prototypes of the hidden insect detector operationally unsatisfactory

DD 1 JAN 73 1473 EDITION OF 1 NOV 65 IS OBSOLETE

معافياتها وتردي الإر

UNCLASSIFIED
SECURITY CLASSIFICATION OF THIS PAGE (When Date Entered)

TABLE OF CONTENTS

INT	DDUCTION	3
	Materials	3 3 5
RES	TS AND DISCUSSION	6
	Adrantage	1
SUMI	ARY AND RECOMMENDATIONS	3
LIT	RATURE CITED	5
APP	NDIX A	7
DIS	RIBUTION LIST	â
1.	TABLES Average Peak and Ramp Heights (mm) of CO, Produced by Three Different Species of Adult Stored Product Insects in a 1-Pound Sample of Whole Grain Wheat with a 5-Minute Purge Cycle and 10-Minute Collect Cycle	9
3.	Peak Heights (mm) of CO ₂ Produced by Adult Red Flour Beetles In a 5-Pound Bag of Flour with a 15-Minute Purge Cycle and 5-Minute Collect Cycle	1
	FIGURES	
1.	Peak Mode Chart Print-Out of a 1-Pound Whole Grain Sample in the Rigid Plastic Cylinder	7
2.	Peak Mode Chart Print-Out of a 5-Pound Packaged Commodity in the Shrink Bag	8

INTRODUCTION

Insect infestations of stored products cause major economic problems throughout the world. Effective stored product insect control requires early, rapid and reliable detection of insect infestations. Various detection methods have been developed including X-ray, 1,2 pheromones to attract insects, 3,4 traps, 5,6 nuclear magnetic resonance, 7 electrical resistance, 8 microwaves, 9 sound, 10,11 and chemical indicators. 12 These methods were not satisfactory because they failed to detect low-level insect infestations in packaged commodities.

The present method for insect detection is outlined in <u>Military Standard 904</u>, <u>Guidelines for Insect Infestation of Subsistence.</u>

Briefly, the method begins with a detailed visual inspection of the package. The contents are then sieved onto a collection surface where the residue is examined for whole insects and insect parts. This procedure destroys the package and its contents and is time consuming.

Bruce and Street¹⁴ described a system which had potential for detection of low-level insect infestations in stored products while maintaining package integrity. The system detected insect-produced carbon dioxide (CO₂) in the presence of atmospheric CO₂. First and second generation prototypes of this system were provided to the United States Army Medical Bioengineering Research and Development Laboratory (USAMBRDL), by the United States Department of Agriculture (USDA) Stored Products Insects Research Laboratory, Savannah, Georgia for laboratory evaluation under simulated operational conditions. The laboratory evaluation of the first prototype is given in Appendix A. This report concerns only the second prototype evaluation.

Purpose

The purpose was to evaluate the capability of the USDA detector system to detect insect infestations in packaged commodities without destroying package integrity. Parameters to be met were that detection occur in a relatively short period of time and that it be uninfluenced by CO₂ from sources outside the package.

Materials

The second prototype is based on a HORIBA Model PIR 2000 General Purpose Infrared Gas Analyzer. This instrument is capable of precision gas analysis based on nondispersive infrared ray absorption for continuously determining the concentration of a given component in a gaseous stream. For insect detection the gas analyzer was preset to detect ${\rm CO}_2$.

Molecules of CO₂ absorb infrared radiation of a specific wavelength. The degree of absorption is proportional to molecule concentration at constant pressure. The infrared radiation emitted by the light source is modulated by a rotating chopper, then passed simultaneously through the sample and reference cells into the detector cell. If the sample cell contains more CO₂ than the reference cells, a decrease in the amount of radiation reaching the sample side of the detector cell results. This difference is registered as an electrical output which is amplified and directed to a meter/recording device.

The recording device, a Linear Model 141, is a multi-range potentiometric null balance servo recorder which provides an accurate, permanent graphic record of signal input. The DC input signal to the recorder is first filtered, then amplified by a preamplifier to a level which is less susceptible to noise and interference. This conditioned signal is then applied to a differential amplifier which continuously compares the conditioned signal to the feedback signal developed by the servo potentiometer. The difference between these two impulses is a positive or negative error signal which is amplified and used to drive the servo motor. The motor is coupled to the servo potentiometer in a direction which reduces the error signal to zero. Since the recorder pen is mechanically coupled with the servo motor and potentiometer, its position on the chart represents an accurate, and continuous graphic record of the input signal.

The insect detector weighs 42 1b and measures 7.5 x 14.5 x 22 in. The accessory equipment included a Drierite rigid plastic cylinder (2.5 x 11 in), two different plastic shrink bags (15 x 21 in and 9 x 15 in), Tygon tubing, Swagelok quick connect fittings, A.C. line filters, a 5-gallon glass jar, and a small wire cage (0.5 x 2 in). A plastic gutter screen (9.5 x 18 in), two wooden strips (0.75 x 9 in) and four No. 10 binder clips were additional accessories used only with the shrink bags.

The commodity test chamber was either the plastic cylinder, when a bulk sample of whole grain was examined, or the shrink bag, when a packaged commodity was tested for insect infestations. The inlet and outlet ports, positioned at opposite sides of the test chambers, were connected to the ends of two segments of Tygon tubing and attached to the insect detector by Swagelok quick connect fittings. The Tygon tubing is fitted with filters to prevent extrinsic particles from entering the detector. The 5-gallon jar, which provides a stable source of air with minimum fluctuations of $\rm CO_2$, had Tygon tubing leading from the jar through the inlet port to a series of pumps which circulated the air through the insect detector. The wire cage facilitated introduction of a known number of insects into the test chamber and their retrieval after

the test. The plastic gutter screen was used to wrap a packaged commodity to create a small air space between the package and shrink bag that allowed air to flow through the package. The wooden strips and binder clips were used to fasten the open end of the shrink bag.

Procedures

The insect detector was operated in the following manner:

Initial Setup

The switches were placed in the following positions:

Power - Off
Purge - Off
Mode - Either Ramp or Peak
Chart Recorder - Off
Recorder Input - 100 MV
Atten - CCW

The line cord of the instrument was plugged into a 115 V AC60 Hz power outlet.

One end of the air inlet hose was attached to the insect detector, and the other end was placed into a 5-gallon jar.

Sample Preparation

Two modes of sample testing were available and selected by means of the front panel Mode switch. The Peak mode first purged the sample and then stopped air flow for a period of time determined by the Test/Collect timer. During the quiescent period the system was sealed. At the end of the Collect interval, flow was restarted and any CO collected in the sample was read out as a peak on the chart recorder.

The Ramp mode was an integrating mode in which air was continuously recirculated around a closed loop containing the sample and the CO, analyzer. In this mode any buildup of CO, was constantly displayed on the recorder chart as an increasing ramp function.

Three species of stored product insects were used as test specimens; the red flour beetle, <u>Tribolium castaneum</u>, the lesser grain borer, <u>Rhizopertha dominica</u>, and the rice weevil, <u>Sitophilus oryzae</u>. During the <u>Tatter part of the investigation</u>, only the <u>red flour beetle was used</u>.


Samples were evaluated by the insect detector using various levels of infestation, species of insects, testing times and modes, and types of commodities. The controls were obtained by placing the samples (packaged or bulk) into a freezer (-50°C) for at least 2 days to assure that no

live insects were present. After removal from the freezer, the samples were allowed to reach room temperature and any condensate to evaporate before placing the contents into the commodity test chamber (shrink bag or plastic cylinder) and connecting the chamber to the insect detector. The infested samples were obtained by artificially introducing a known number of laboratory reared beetles into those samples which had previously been used as the controls. Both the Ramp and Peak modes were tested. Measurements were made of the peak and ramp heights which were recorded on the strip chart. These were examined to ascertain if there were detectable differences between the two modes of operation, and to determine if the peak and ramp heights consistently corresponded to a given number of artificially introduced insects in a sample.

RESULTS AND DISCUSSION


The Peak mode was generally more sensitive, 15 but required a fixed time cycle. Until the end of the cycle no information was available on the degree of infestation. The ramp mode, although not as sensitive, had the advantage of faster presentation of data. As soon as a positive slope on the ramp was established the test could be terminated. In the case of a heavily infested sample the test could be terminated in as little as 15 to 20 seconds. Field experience would determine whether either or both modes are desirable in a commercially produced system.

Typical Peak mode chart print-outs using the plastic chamber and the shrink bag are given in Figures 1 and 2, respectively. The plastic chamber was used for a 1-pound sample of whole grain wheat. The shrink bag was used for a 5-pound bag of flour or corn meal. The initial peak occurred each time either commodity chamber was opened to external air. Thus, when the insect detector was turned on to begin the test, this excess air was pumped through the ${\rm CO_2}$ detector to flush the system. The CO2, included in this bolus of air, caused the recorder pen to rise sharply before returning to baseline. This process usually took 20 seconds or less with whole grain. The short "purge" time is made possible because of the large amounts of interstitial air in a sample of whole kernel grain. With flour or corn meal, which had comparatively little interstitial air and was compacted when under vacuum, 10 to 15 minutes were needed for the system to purge and establish a steady baseline. This was essential before any sample could be tested for the presence of CO₂. A false reading was recorded if a test was conducted without adequate purging. After the initial "purge" peak, the baseline would level out during the rest of the purge cycle. The system then entered a collect phase where CO₂ was allowed to accumulate in the sample. At the end of the collect cycle, the system was flushed again. The CO₂



- A Initial peak caused by opening the commodity test chamber to add or change a sample.
- B Purge cycle flushing the system of any remaining gases from the previous run or those which entered while the test chamber was opened. Air was pumped through from an external air source.
- C Collect cycle the detector was sealed off with no additional external air pumped through the system.
- D Peak height indicates amount of internally produced CO₂.
- Figure 1. Peak Mode Chart Print-Out of a 1-Pound Whole Grain Sample in the Rigid Plastic Cylinder.

delication was well-



- A Initial peak caused by opening the commodity test chamber to add or change a sample.
- B Purge cycle flushing the system of any remaining gases from the previous run or those which entered while the test chamber was opened. Air was pumped through from an external air source.
- C Collect cycle the detector is sealed off with no additional external air pumped through the system.
- D Peak height indicates amount of internally produced CO₂.

Figure 2. Peak Mode Chart Print-Out of a 5-Pound Packaged Commodity in the Shrink Bag.

given off from the sample in the commodity test chamber was recorded as a peak on a strip chart print-out. In this investigation the assumption was made than an insect infestation would produce the ${\rm CO}_2$ and that the magnitude of the peak would be directly related to the number of insects present.

The insect detector could detect adult insect infestation in a 1-pound sample of whole grain wheat (Table 1) with some variations. Using the Ramp mode, the insect detector recorded a greater ramp height with commodities containing three rice weevils (12.00 mm) than with five rice weevils (8.32 mm). This seemingly indicated that three rice weevils produced more $\rm CO_2$ than five rice weevils.

TABLE 1. AVERAGE PEAK AND RAMP HEIGHTS (mm) OF CO2 PRODUCED BY
THREE DIFFERENT SPECIES OF ADULT STORED PRODUCT INSECTS
IN A 1-POUND SAMPLE OF WHOLE GRAIN WHEAT
WITH A 5-MINUTE PURGE CYCLE AND 10-MINUTE COLLECT CYCLE

Beetles Ramp Peak Ramp Peak Ramp 0 0.00 1.00 0.00 2.50 0.00 1 0.66 2.00 1.32 3.32 0.00 2 1.66 2.32 0.00 3 5.32 6.50 12.00 1.32 5 13.66 8.32 3.00	No.	Red Flour Mod	r Beetles de	Rice Wo		Lesser Grain Borers Mode		
1 0.66 2.00 1.32 3.32 0.00 2 1.66 2.32 0.00 3 5.32 6.50 12.00 1.32 5 13.66 8.32 3.00	Beetles	Ramp	Peak ^a	Ramp	Peak	Ramp	Peak	
2 1.66 2.32 0.00 3 5.32 6.50 12.00 1.32 5 13.66 8.32 3.00	0	0.00	1.00	0.00	2.50	0.00	3.32	
3 5.32 6.50 12.00 1.32 5 13.66 8.32 3.00	1	0.66	2.00	1.32	3.32	0.00		
	2	1.66		2.32		0.00		
	3	5.32	6.50	12.00		1.32	9.00	
6 10 50 - 7 66 -	5	13.66		8.32		3.00	13.00	
19.30 00.7	6	-	19.50		7.66			

a. Five-minute purge, 5-minute collect.

Both modes involved a considerable expenditure of time. To decrease the time required to test a sample, the collect time was reduced from 10 to 5 minutes using the Peak mode. This reduced the sensitivity of the instrument, but it still could detect differences in red flour beetle or rice weevil infestation levels. The insect detector required a 10 minute collect time for samples containing the smaller lesser grain borer, which probably produced lesser quantities of CO₂ per individual.

The initial tests were conducted using whole grain wheat to learn how the detector reacted to different levels of insect infestation. However, the main interest of the Department of Defense and the major objective of this report was to evaluate the effectiveness of the insect detector in determining various levels of insect infestations in processed commodities. Additional tests were performed using the red flour beetle in 5-pound bags of corn meal and flour because fewer of these insects are allowed in processed food commodities. According to Military Standard 904, 13 a product in a military wholesale food facility can contain a maximum of six insects per pound of product unless the infestation involves Tribolium or Trogoderma insects, the limits of which are three and zero, respectively. However, any level of insect infestation would bar acceptance of a processed commodity by The Department of Defense.

Further tests were conducted using a beetle-infested 5-pound bag of corn meal at five different temperatures (20°-27°C) to simulate temperature fluctuations generally found in government warehouses. The results confirmed that red flour beetles respired more at 27°C than at 20°C (Table 2) as indicated by increased peak heights. These results agree with the observations by Hunter and Hartsell, 16 who found that increasing the temperature would increase $\rm CO_2$ production in larvae of another stored product insect, Plodia interpunctella.

TABLE 2. PEAK HEIGHTS (mm) OF CO. PRODUCED BY ADULT RED FLOUR BEETLES IN A 5-POUND BAG OF CORN MEAL WITH A 15-MINUTE PURGE CYCLE AND 5-MINUTE COLLECT CYCLE

	Temperatures										
No. Beetles	2	ე° C	21'	°C	24'	,c	25	°C	27'	°C	Average 20°-27°C
0	1	0	4	1	1	0	3	2	0	2	1.4
1	1	0	3	1	0	1	3	2	3	1	1.5
14	4	4	4	4	4	4	8	6	8	3	5.2
15	2	4	3	4	6	4	7	5	5	2	4.3
30	6	11	9	8	10	8	9	4	8	9	8.2
45	9	6	12	8	14	11	10	6	17	16	10.9

With a certain degree of accuracy, repeatable results of peak heights corresponding to different levels of insect infestations were obtained by the insect detector, but there were variations. An uninfested sample

could be distinguished from one with 15 red flour beetles (three insects per pound). The detector could not accurately differentiate between a sample having 14 beetles or 15 beetles nor between samples containing 1 beetle as opposed to 0 beetles. The results of tests conducted using a beetle infested 5-pound bag of flour at two different temperatures (24°-26°C) are given in Table 3. Fewer replications were conducted, but these results supported the findings of the tests conducted with samples of corn meal.

TABLE 3. PEAK HEIGHTS (mm) OF CO₂ PRODUCED BY ADULT RED FLOUR BEETLES IN A 5-POUND BAG OF FLOUR WITH A 15-MINUTE PURGE CYCLE AND 5-MINUTE COLLECT CYCLE

	Tempera tures						
No. Beetles	24°C		26	Average 24°-26°			
0	2	1	0	2	1.3		
1	2	3	0	4	2.3		
14	5	4	6	6	5.3		
15	5	4	3	4	4.0		
30	5	5	7	8	6.3		
45			17	12	7.3		

Advantage

The insect detector was able to distinguish the difference between an uninfested sample and a sample which contained three <u>Tribolium</u> sp. (red flour beetles) per pound or six of any other genera of insects per pound of food commodity. These figures represent the maximum number of insects allowed in a stored food product in a military wholesale food facility.

Disadvantages

- 1. The insect detector could not detect low-level insect infestations in 5-pound packaged commodities or 1-pound samples of whole grain within a reasonable length of time (less than 5 minutes).
- 2. With whole grain samples a stable baseline could be established in 10 to 30 seconds while 10 to 15 minutes were required for baseline stabilization in packaged commodities.

- 3. The time required to establish a stable baseline obviously increased sample run time. A whole grain sample could be tested in 10 minutes or less but a packaged commodity would usually take at least 20 minutes. Additional time was required if more replications were desired.
- 4. There were variations in the recorded results.
- 5. If the machine was jarred only slightly, a false peak would be recorded. If the insect detector was placed on an unstable table or cabinet the baseline would be broad and wavy.
- 6. The sample chamber (shrink bag or plastic container) had to be placed on a cushioned surface away from the machine. This reduced the vibrations caused by the operation of the insect detector. The vibration reduced the respiration rate of the insects thereby reducing ${\rm CO}_2$ production which caused smaller peaks to be recorded.
- 7. The insect detector, capable of measuring $\rm CO_2$, could not detect dead insects, insect parts, differences in species or their stage of development, 17 , 18 or other contaminants in packaged commodities. Also, lower temperatures decreases the respiration rates ($\rm CO_2$ production) of insects. 16
- 8. Any source of CO₂ near the machine caused it to register peaks on the recorder. If the operator stayed within 1 or 2 feet of the machine, peaks would be recorded from the CO₂ given off by the operator. The detector worked best when the operator set the machine to run a sample and left the vicinity. A solution to this problem would be to connect a closed source of air to the inlet port on the back of the insect detector.
- 9. Sometimes negative slopes were recorded when the Ramp mode was used.
- 10. The timer for the purge cycle was capable of running only a maximum of 5 minutes. Fifteen minutes were necessary to purge a stored product packaged commodity to obtain a stable baseline. Another timer could be installed to remedy this problem.
- 11. The shrink bag should be only slightly larger than the commodity to be examined. This would reduce some of the time it took for the bag to collapse around the commodity. Several different sized shrink bags would be necessary to accommodate different sized packages. Also, the best position of the inlet and outlet ports of the shrink bag varies for different commodities.
- 12. The inlet and outlet ports frequently collapsed against the bag and blocked the air flow. The operator then had to manually pull the bag away from the ports.

13. The shrink bag was made of very thin plastic which could be torn. Also, there may have been some leakage of air through this material.

SUMMARY AND RECOMMENDATIONS

The second prototype of the hidden insect detector showed much improvement over the first prototype. However, the second prototype still was unable to meet required performance criteria. The second prototype conceptually was technically usable and could detect three insects per pound of commodity, but other physical and mechanical problems made it operationally unacceptable. A system which had the same basic principle of operation, but was more refined to eliminate and minimize undesirable characteristics could have potential in detecting hidden insect infestations in military stored product warehouses. However, since live insects are not the only contaminants for which examinations must be conducted, it appears unlikely that such a device will ever replace manual inspection.

LITERATURE CITED

- 1. Milner, M., M.R. Lee, and R. Katz, "Application of X-ray Technique to the Detection of Internal Insect Infestations of Grain," <u>J. Econ. Entomol.</u>, 43(6):933-935 (1950).
- 2. Dobie, P., "An Investigation into the Use of an X-ray Technique in the Study of Pre-emergent Stages of Sitophilus oryzae (L.) Developing in Manitoba Wheat," J. Stored Prod. Res., 9:7-12 (1973).
- 3. Burkholder, W.E., "Applications of Pheromones for Manipulating Insect Pests of Stored Products," Proc. Symp. Insect Pher. Appl., Nagaoka and Tokyo, Dec. 8-11, 1976, 111-122.
- 4. Burkholder, W.E., "Manipulation of Insect Pests of Stored Products," pp. 345-351, in H.H. Shorey, et al (eds.), John Wiley and Sons, Inc., NY, NY (1977).
- 5. Loschiavo, S.R., "Laboratory Studies of a Device to Detect Insects in Grain, and of the Distribution of Adults of the Rusty Grain Beetle, Cryptolestes ferrugineus (Coleoptera:Cucujidae), in Wheat-Filled Containers," Can. Entomol., 106(12):1309-1318 (1974).
- 6. Loschiavo, S.R., "Field Tests of Devices to Detect Insects in Different Kinds of Grain Storage," <u>Can. Entomol.</u>, 107:385-389 (1975).
- 7. Street, M.W., "Nuclear Magnetic Resonance for Detecting Hidden Insect Infestation in Stored Grains," J. Ga. Entomol. Soc., 6(4):249-254 (1971).
- 8. Wirtz, L.A. and J.A. Shellenberger, "A Rapid Method to Determine Insect Infestation in Grain Using Electricity," <u>Cereal Sci. Today</u>, 8(9):305-318 (1963).
- 9. Hamid, M.A.K., C.S. Kashyap, and R. van Cauwenberghe, "Control of Grain Insects by Microwave Power," <u>J. Microwave Power</u>, 3(3):126-135 (1968).
- 10. Adams, R.E., J.E. Wolfe, M. Milner and J.A. Shellenberger, "Aural Detection of Grain Infested Internally with Insects," <u>Science</u>, 118(305): 163-164 (1953).
- 11. Street, M.W., "A Method for Aural Monitoring of In-Kernel Insect Activity," J. Ga. Entomol. Soc., 6(2):72-75 (1971).

- 12. Dennis, N.M. and R.W. Decker, "A Method and Machine for Detecting Living Internal Insect Infestation in Wheat," <u>J. Econ. Entomol.</u>, 55(2):199-203 (1962).
- 13. U.S. Department of Defense, Military Standard Guidelines for Insect Infestation of Subsistence, 7 pages (1975).
- 14. Bruce, W.A. and M.W. Street, "Infrared CO. Detection of Hidden Insects," J. Ga. Entomol. Soc., 9(4):260-265 (1974).
- 15. Street, M.W., Personal Communication (1979).
- 16. Hunter, D.K. and P.L. Hartsell, "Influence of Temperature on Indian-Meal Moth Larvae Infected with a Granulosis Virus," J. Invert. Pathol., 17:347-349 (1971).
- 17. Williams, J.H. and D.A. Wilbur, "Respiratory Environments of Grain Infesting Weevils. I. Comparison of Culture-Jar and Laboratory Rearing-Room Atmospheres," J. Econ. Entomol., 61(2):345-348 (1968).
- 18. Williams, J.H. and D.A. Wilbur, "Respiratory Environments of Grain-Infesting Weevils. II. Comparison of Respiratory Atmospheres Produced by Laboratory Populations of Three Species of Grain Weevils," J. Econ. Entomol., 62(3):693-697 (1969).

APPENDIX A

COMMENTS CONCERNING THE FEATURES AND CHARACTERISTICS OF THE RAPID NON-DESTRUCTIVE STORED PRODUCTS INSECT DETECTOR SYSTEM (FIRST PROTOTYPE)

<u>Advantages</u>

- 1. Instrumentation and carbon dioxide detector appeared to have adequate sensitivity for detection of carbon dioxide concentrations and to changes in concentrations in bulk commodity sample handling systems.
- 2. Instrumentation demonstrated the capability to detect, display and record small changes (0.25 ppm) in carbon dioxide level with relatively short collect times when bulk product samples evaluated had relatively large interstitial spaces.
- 3. In the laboratory it was demonstrated that, with unpackaged bulk products with relatively large interstitial spaces, repeatable results could be rapidly obtained.
 - 4. Printer provided an easily readable, rapid print-out of results.

Disadvantages

- 1. Results using this system with processed agricultural products having little interstitial space and capable of being compacting were unreliable and often not repeatable.
- 2. Purge time requirements (greater than 6 minutes) for processed products were excessive.
- 3. Leakage of vacuum from the shrink bag was inherent in this system. Degree of leakage varied considerably from run to run.
- 4. Initial design shrink bag provided with this system had valves which interfered with the sealing of the pack. This pack also ripped during initial testing.
- 5. System is too bulky. Weight and bulk could be reduced by rearranging components. Vacuum lines were longer than required.
- 6. Instrumentation required in excess of 30 hours for complete warm-up and stabilization of the baseline. To accommodate this, the system has to be on 24 hours per day.

- 7. The system is dependent on a 110/120 volt, 60-cycle electrical system, thus limiting its operating environment.
- 8. Internal insect infestation of the instrument could and did develop. However, this was noted only in the replaceable internal filter elements.
- 9. Instrumentation is sensitive to movement. Chart recordings reflected and plotted even slight movement of the system. If the instrument is moved during operation, additional stabilization time is required.
- 10. Changes in the ${\rm CO}_2$ in the surrounding environment interfered with the accuracy of the readings.

DISTRIBUTION LIST

Project No. 3\$162778A838/00/025

No. of Copies	Addressee
2	Preventive Medicine Division ATTN: Medical Zoology Branch Academy of Health Sciences Fort Sam Houston, TX 78234
1	Executive Secretary Management Armed Forces Pest Management Forest Glen Section, WRAMC Washington, DC 20012
1	Head, Environmental Quality Branch Occupational & Preventive Medicine Division (553) Bureau of Medicine and Surgery Washington, DC 20372
1	HQ PACAF/DEMM ATTN: Mr. Jonathon T. Kajiwara Hickham AFB, HI 96853
12	Defense Technical Information Center Alexandria, VA 22314
1	Defense Personnel Support Center ATTN: DPSC-STQ 2800 South 20th Street Philadelphia, PA 19101
1	Department of Entomology 10th Medical Laboratory APO NY 09180
1	Directorate of Facilities Engineering US Army Support Command, Hawaii ATTN: AFZV-FE-BG Fort Shafter, HI 96858
1	Disease Surveillance Branch (Entomology) Epidemiology Division USAF School of Aerospace Medicine Brooks AFB, TX 78235

No. of Copies	Addressee
1	Officer in Charge Disease Vector Ecology and Control Ctr Naval Air Station, Box 43 Jacksonville, FL 32212
1	HQ, USA TRADDOC ATTN: ATEN-FE-BG Fort Monroe, VA 23651
4	Defense Pest Management Information and Analysis Center Forest Glen Section Walter Reed Army Medical Center Washington, DC 20012
1	Naval Facilities Engineering Command Environmental Branch, Northern Division US Naval Base, Bldg 77 Philadelphia, PA 19112
2	Naval Facilities Engineering Command Biological Sciences Staff ATTN: Code 112B 200 Stovall Street Alexandria, VA 22332
1	Officer in Charge, Naval Air Station Naval Disease Vector Ecology & Control Ctr Alameda, CA 94501
1	Office of Chief of Engineers ATTN: Entomologist Ft. Belvoir, VA 22060
2	Office of the Surgeon General ATTN: Entomology Consultant/DASG-HCH-E Washington, DC 20310
1	USAEHA, Regional Division - West ATTN: Radiation & Entomological Sci Br Fitzsimons Army Medical Center Denver, CO 80240
1	USAEHA, Regional Division - South ATTN: Radiation & Entomological Sci Br Fort McPherson, GA 30330

No. of Copies	<u>Addressee</u>
1	USAEHA Regional Division - North ATTN: Radiation & Entomological Sciences Br Ft. Meade, MD 20755
1	US Army Health Services Command Medical Entomology Consultant Health and Environment Division Fort Sam Houston, TX 78234
2	USAMBRDL Technical Library Ft. Detrick, Frederick, MD 21701
1	US Army Materiel Development and Readiness Command ATTN: DRCSG-E 5001 Eisenhower Avenue Alexandria, VA 22333
1	Office of the Engr/Facilities Engr Div Buildings & Grounds Branch HQ, Eighth US Army APO San Francisco, CA 96301
1	HQ, US Army Japan/IX Corps ATTN: AEAEN-EH Office of the Engineer APO New York 09403
1	HQ, US Army Forces Command ATTN: AFEN-FE-S Fort McPherson, GA 30330
1	USA MEDDAC Preventive Medicine Activity Canal Zone APO Miami 34008
1	USA MEDDAC Preventive Medicine Activity Fort Leonard Wood, MO 65473
1	HQ 193rd Inf. Bde. ATTN: AFZUFE-BE Julio Mendez, Engineer Entomologist Box 923 APO New York 34004

No. of Copies	Addressee
2	Commander US Army Medical R&D Command ATTN: SGRD-SI/Mrs. P. Madigan Fort Detrick Frederick, MD 21701
1	Dr. John Reinert USDA 1600 SW 23rd Dr. Gainesville, FL 32604

ACHY MEDICAL BIOENGINEERING RESEARCH AND DEVELOPMENT --ETC F/6 6/5
LABORATORY EVALUATION OF THE USDA RAPID NONDESTRUCTIVE STORED P--ETC(U)
FEB 80 L M ANDERSON, J H NELSON
UNCLASSIFIED
USAMBROL-TR-8001
NL

END
(N-B)

OTIC

SUPPLEMENTARY

INFORMATION

ERRATA SHEET

Reference;

TECHNICAL REPORT 8001

LABORATORY EVALUATION OF THE USDA RAPID NONDESTRUCTIVE STORED PRODUCTS INSECT DETECTOR

US ARMY MEDICAL BIOENGINEERING RESEARCH AND DEVELOPMENT LABORATORY Fort Detrick, Frederick, MD 21701

Page 13, SUMMARY AND RECOMMENDATIONS

Line 9, delete last sentence in toto "However, since live insects . . . manual inspection."